

STD. SIZES	CENTERLINE DIMENSIONS		WEIGHT
GS5	12"W x 18"H x 12"L	LIFT OFF UNIT	35
GS-1	12"W x 24"H x 24"L	LIFT OFF UNIT	40
GS-2	12"W x 24"H x 32"L	LIFT OFF UNIT	45
GS-3	12"W x 24"H x 42"L	HINGED UNIT	51
GS-4	18"W x 30"H x 48"L	HINGED UNIT	67

GS = POWDER-COATED STEEL GUARDSHACK OR APPROVED EQUAL

NOTES:

- 1. AFTER ALL WELDING, ENTIRE UNIT SHALL BE PROCESSED WITH IRON PHOSPHATE PRE-TREATMENT. ELECTROSTATIC APPLICATION OF POWDER SHALL BE FUSION BONDED. POWDERCOAT COLOR SHALL BE BLACK.
- ALL BOLTS FOR HINGES AND HASPS SHALL BE ZINC-PLATED TAMPER PROOF, EXCEPTION -USE SS HARDWARE FOR SS UNITS.
 SS = STAINLESS STEEL
- 3. REFER TO SPECIFICATIONS FOR MODEL NUMBER
- 4. REFER TO CITY STANDARD DETAIL LSD-14 FORALL MATERIALS

			CIT	Y OF	FREMO	ONT	DATE APPROVED BY CITY COUNCIL 04/11/06		
				STANDARD DETAILS		RESOLUTION NO. 2006-31			
			CITY STANDARD						
110	DE #055	DATE	BACKFLOW PREVENTOR				11 11 1.		
NO.	REVISED	DATE	UNIT ENCLOSURE				Man Highes		
REVISIONS			<u>UNIT ENCLUSURE</u>			CITY ENGINEER			
FILE NO. LSD	-17.DWG	1/2" =	: 1'-0"	DRAWN AK/MM/PN	CHECKED RER	NOV. 2005	DWG NO. LSD-17	17 of 27	